





5-TON COOLING CAPACITY!



5-TON ECU EU-VOLTAGE

MODEL NUMBER: AK-ECU-5T-EU



- Nominal 17.5 kW Cooling Capacity
- 16 kW of Heating Standard (12 kW Optional)
- 3-Year Warranty
- Scroll Compressor Technology
- Hot gas, by-pass valve for optimum performance
- Supply / return air-ducts included
- Micro-Channel Condensor Coil
- Direct drive, backward inclined airfoil impeller (not belt driven)
- Stackable to 6 high
- Operational from -31°C to +55°C / 50 Hz or 60 Hz
- UL1995 and CSA C22.2 No. 236-05 Certified

POWER CONSUMPTION CHART

230/400V, 50 Hz, 3 Phase, 5-wire

COMPONENT	FLA
Compressor	13.9 amps
Evaporator Motor (1 hp)	2.0 amps
Condenser Motor (½ hp)	1.4 amps
Heater (16.0 kW)	22.2 amps
Heating Mode	24.5 amps
Cooling Mode	19.0 amps
Auto Mode	24.5 amps

POWER SPECIFICATIONS

Voltage	230/400
Frequency	50 Hz or 60 Hz*
Number of Phases	3
Number of Wires	5

*Specifications shown were measured at 50 Hz

PERFORMANCE SPECIFICATIONS

Static Pressure	Air Flow
25.4 mm H ₂ O	52.39 m ³ /min
30.5 mm H ₂ O	51.75 m ³ /min
38.1 mm H ₂ O	48.14 m ³ /min

PHYSICAL DIMENSIONS

Height	619.3mm	Depth	1060.5mm
Width	1314.5mm	Weight	224.5kg

COOLING CAPACITY

51.7°C Ambient Temperature

Interior Shelter Temp.	Relative Humidity	Capacity
26.7°C DB	50%	16.340 kW
23.9°C DB	50%	16.076 kW



Alaska 5-Ton ECUs can be stacked 4 high/16 per 463L pallet for volume transport.



TOLL FREE **+1-888-370-1800**
TEL **+1-425-889-1205**

WWW.**AKS**.COM