

TowTank

Rapidly deployable, robust towable tanks for the storage and transport of hydrocarbons.



5m³ / 5 Tonne (lift-able)



10m³ / 10 Tonne (lift-able)



20m³ / 20 Tonne



50m³ / 50 Tonne

Specifications

Capacity M ³	5 M ³ lift-able	10 M ³ lift-able	20 M ³ Tow only	30 M ³ Tow only	50 M ³ Tow only	100 M ³ Tow only
Capacity US Gal	1,320	2,640	5,280	7,925	13,208	26,416
Dimensions	2.1 x 5.7m	2.1 x 9.4m	2.8 x 11.0m	2.8 x 16.5m	3.4 x 18.0m	4.1 x 25.0m
Bow flotation	1	1	1	1	1	1
Side flotation	2	2	2	2	2	2
Fill & Discharge fittings	2	2	3	4	4	6
Vent fitting	1	1	1	1	1	2
Grab handles	6	10	10	14	14	18
Securing points	-	2	3	4	4	6
Dry weight Kg	175	235	380	460	580	930
Packaged size	2.3 x 1.0 x 0.8m	2.3 x 1.0 x 1.0m	2.2 x 1.4 x 1.3m	2.2 x 1.4 x 1.3m	2.4 x 1.4 x 1.5m	2.4 x 2.0 x 1.8m

Key Benefits

- Speed and ease of deployment with the minimum of personnel and equipment.
- Stable and maneuverable at good speeds; up to 15 knots empty, 7 knots full.
- Robust temporary storage for use at sea or on land.
- Able to be decontaminated following use.



103 Central Park Drive
Henderson
PO Box 19111, Avondale
Auckland, New Zealand

T +64 9 836 8255
F +64 9 836 8256
W www.covertex.co.nz
E sales@covertex.co.nz